



CP-WX3011N

HITACHI
Inspire the Next



Key Features

- 3,000 ANSI Lumens
- Native WXGA Resolution
- 2000:1 Contrast Ratio
- 7.9 lbs.
- Microphone input with amplifier
- Network control, maintenance and security
- Network Bridge RS232 control
- Lamp life approximately 6,000 Hours (Eco Mode)*
- HDMI / Component / Composite / S-Video Inputs
- Stand-by Audio
- 16W Speaker Output
- 0.5 watt power saving mode using 120V
- Template Function
- 2 RGB In, 1 RGB out / Composite / S-Video
- USB connection to computer
- PC-less presentation
- Network Messenger
- Present content via LAN
- 29 dB (Eco Mode)



Specifications

Model Name	CP-WX3011N Series
Liquid Crystal Panel Structure	0.63" polysilicon active-matrix TFT x 3
Number of Pixels	1,024,000 pixels
Resolution	540 TV lines
	1280 dots X 800 lines
Colors	16.7 million colors
Aspect Ratio	Native 16:10
Lens	Manual zoom x 1.2
Throw Ratio (distance : width)	1.8 : 1
Lamp	210W UHB
Brightness	3,000 ANSI Lumens
Expected lamp Life	Approximately 3,000 hours (normal) 6,000 hours (Eco mode)*
Contrast Ratio	2000 : 1 (using active IRIS)
Speaker Output	16W (2 x 8W speakers)
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption	330W
Operating Temperature	5°C - 35°C (41°F - 95°F)
Input Signals	RGB Composite Video Component Video
	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC 13", MAC 16" NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N 480i, 576i, 480p, 720p, 1080i, 1080p
Acoustic Noise Level	35 dB (29 dB in Eco Mode)
H-Sync	15 Hz - 106 Hz
V-Sync	50 kHz - 120 kHz
Vertical Keystone	+ / - 30°
Approvals	UL, C-UL, FCC, CE, RoHS
RGB Input	Analog RGB
RGB Output	RGB
Digital Input	HDMI x 1
Video Input	S-Video Composite Video Component Video
	Mini DIN 4-pin connector x 1 RCA jack x 1 RCA jack x 3
Audio	Input
	Stereo Mini jack x 2, RCA(L/R) x 1 pair, Microphone Jack(stereo mini) x 1 RCA(L/R) x 1 pair
	Output
Ethernet	RJ-45 port / 100 base-T
Control Terminals	9-pin D-sub connector x 1 (RS-232 control)
Other	USB-A, USB-B (USB Mouse)
Dimensions (W x D x H)	12.5" x 3.9" x 11.3"
Weight	7.9 lbs.
Closed Caption	CC1, CC2, CC3, CC4, T1, T2, T3, T4
Additional Features	Kensington Slot, Digital Gamma Correction, Whiteboard / Blackboard More, Input Source Naming., MyMemory / MyScreen / MyButtons / MyText, Auto V Keystone, Serial Number on Side
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual
Lamp	CPX2010LAMP (DT01021)
Remote Control	HL02483
Filter	MU06481



Screen Size 16:10 Throw Distance

Diagonal*	Width*	Min*	Max*
30	25	35	43
60	48	73	89
80	64	99	121
100	80	125	152
120	96	151	183
150	120	190	229
200	160	254	307
300	240	383	463

Throw Ratio: 1.5 - 1.8:1 (distance : width)
*Measured in inches

